

Custom Breathing Air Compressor Trailer Package Including Generator, Compressor, Fill Station and Cascade Storage.

Mako model BAM06H-E1 Breathing Air Module compressor package including:

- Four stage, air-cooled compressor (14.0 cfm @ 6000 psi)
- 10 Horsepower electric motor (230V/60Hz/ 1 phase)
- UL listed electric panel
- Direct online IEC starter package
- PLC controller
- Instrumentation / controls:
 - High air temperature switch
 - Low oil pressure switch
 - Start/stop air pressure switch
- Gauge panel including:
 - Hour meter
 - High air temperature warning light
 - Low oil pressure warning light
 - High air pressure light
 - Emergency stop button
 - Final stage pressure gauge
- MK2C purification system (processes 34,200 cf w/ an 70 F inlet)
- CO/Moisture indicator kit
- Automatic condensate drain with muffler reservoir
- Enclosed, insulated, vertical cabinet
- Hinged access door in front
- Removable, hinged access doors on sides
- 1/2" JIC male outlet fitting
- Weight: 1160 lbs

Updated 9/22

OPTIONAL ELECTRONIC COMBINATION

CO/MOISTURE MONITOR

- Tamper-proof electronic CO/moisture monitor with automatic shutdown
- Calibration kit included
- Factory installed

NOTE: CO monitor is a requirement under NFPA 1989

Mako model SSCFS2-4HP Two position, SCBA/Scuba, containment fill station including:

- Two position, front loading, containment fill station capable of holding a 120 cf 3500 psi Scuba cylinder
- Latching front door with safety interlock
- Two fill whips with isolation valves, bleed valves and SCBA fill adapters
- Fill panel including:
 - Regulator complete with push action valve
 - Inlet and outlet gauges
 - Color zoned gauges
 - Safety relief valve on outlet of regulator set at 4700 psi
- One fill control valve and gauge
- 4 bank cascade control with "to" and "from" valves
- Bypass valve
- Regulated auxiliary outlet with valve and high pressure male coupler
- Embedded silk screen air flow schematic
- Weight: 1077 lbs

509 CF ISO/UN 6000 PSI STORAGE CYLINDERS

Westinghouse WGen12000DFc - 12,000 Watt Electric Start Dual Fuel Portable Generator w/ CO Sensor & Wireless Remote Start (CARB)

Voltage - 120/240 Single-Phase

Frequency - 60 Hertz

Rated Watts - 12000 Watts

Surge Watts - 15000 Watts

Fuel Type - Gasoline/LP

LP Power Capacity - 10800 Watts

Rated Amps - 50 Amps

Reliance Controls 50-Amp (Straight Blade / Twistlock 120/240V) Generator Power Cord (25-Foot)

V-Nose Front With Solid Front Wall Construction

Rear Ramp Door & Spring Assist

32" Side Door With RV Flush Lock With Keys

Thermacool Ceiling

Interior 12 Volt Dome Light With Switch

Non Powered Roof Vent Braced For A/C

24" ATP Stoneguard Front

ATP Stoneguard Strip Up Point Of V-Nose

(2)3500 LB. 4" Drop Leaf Spring Axles With Electric Brakes On Both Axles

E-Z Lube Hub Axles
Aluminum Tear Drop Fenders
New St205 15" Bias Ply Tires
Silver Modular Wheels
Screwed Exterior
.024 Gauge Aluminum Exterior With Baked Enamel
Finish
Heavy Duty Exterior Trim
Wrapped Galvalume Roof (No Screws In Top Of Roof)
High Tech Roof Sealant
2 3 Steel Tube Main Frame
2 X 3 Steel Tube Cross Members
3" Flat Steel Backer Plate Welded Around The Bottom
Of Every Wall
1 & 1/2" X 1" Square Steel Tubing Wall & Ceiling
Frame
Floor & Walls On 16" Centers
Ceiling On 24" Centers
Premium 3/8" Finished Plywood Walls
3/4" Treated Plywood Floor
6' Interior Height
2 & 5/16" Coupler
7 Way Bergman Plug
Battery Backup Breakaway Kit
Welded Safety Chains
2000 LB. Tongue Jack With Sand Foot
Dot Required Lights
Rear Tag Light
Sealed LED Tail Light & A Complete Manufacturer's
Warranty.

Installation of equipment listed in the proposal